

IN THE CLAIMS:

Please cancel Claims 2 and 8 without prejudice or disclaimer of subject matter, and amend Claims 1, 4, 7 and 9 as shown below. The claims, as pending in the subject application, read as follows:

1. (Currently Amended) A color conversion method of inputting first and second color difference values and obtaining a corresponding saturation value, comprising steps of:

creating a main lookup table which stores saturation values for color difference values, and a sub-lookup table for obtaining a value corresponding to the first color difference value for accessing the main lookup table, wherein the first color difference value is equal to or less than the second color difference value;

accessing the sub-lookup table with the first color difference value to obtain the value corresponding to the first color difference value;

determining an address of the main lookup table in correspondence with the first and second color difference values on the basis of the ~~value obtained from the sub-lookup table~~ value obtained in the accessing step and a difference between the first and second color difference values; and

obtaining a saturation value corresponding to the first and second color difference values by accessing the main ~~look-up~~ lookup table ~~using~~ with the address determined in ~~said~~ the determining step.

wherein the main lookup table has a smaller number of entries than the number of all possible combinations of the first and second color difference values by utilizing symmetry of the saturation value for the first and second color difference values.

2. (Cancelled)

3. (Previously Presented) The method according to claim 1, wherein the sub-lookup table stores an address of the entry in which the first and second color difference values are the same.

4. (Currently Amended) A lookup table for obtaining an output value defined for an input value, comprising:

a main lookup table adapted to, when a definition of an output value has or is regarded to have symmetry for a plurality of input values, or when a combination of the plurality of input values is limited by a specific existence condition, store the output values for the plurality of input values in consideration of at least one of the symmetry and the specific existence condition; and

a sub-lookup table adapted to store an address of an entry in which a first input value and a second input value of the plurality of input values are the same,

wherein the address of ~~said~~ the main lookup table is determined on the basis of an address obtained ~~from~~ by accessing ~~said~~ the sub-lookup table ~~[[by]]~~ with the first input value being equal or less than the second input value of two arbitrary input values

and a difference between the first and second input values, in correspondence with the two arbitrary input values, and

wherein the main lookup table has a smaller number of entries than the number of all possible combinations of the first and second input values by utilizing symmetry of the output value for the first and second input values.

5. (Original) The table according to claim 4, wherein the specific existence condition includes a color space.

6. (Original) The table according to claim 4, wherein the output value includes a saturation in a color space determined in advance.

7. (Currently Amended) An image processing apparatus for inputting image data and obtaining a corresponding saturation value, comprising:

calculation means for calculating a color difference value of each pixel of the input image data;

a main lookup table adapted to store saturation values for the color difference values;

a sub-lookup table adapted to obtain a value corresponding to a first color difference value being equal or less than a second color difference value, for accessing ~~said~~ the main lookup table in correspondence with the first color difference value;

determination means for accessing the sub-lookup table with the first color difference value to obtain the value corresponding to the first color difference value and for

determining an address of ~~said~~ the main lookup table in correspondence with the first and second color difference values of pixels calculated by ~~said~~ the calculation means, on the basis of the value corresponding to the first color difference value obtained ~~from~~ by ~~said~~ the sub-lookup table ~~by the first color difference value~~ and a difference between the first and second color difference values; and

read means for accessing ~~said~~ the main lookup table ~~on the basis of~~ with the address determined by ~~said~~ the determination means and reading out a saturation value corresponding to the first and second color difference values,

wherein the main lookup table has a smaller number of entries than the number of all possible combinations of the first and second color difference values by utilizing symmetry of the saturation value for the first and second color difference values.

8. (Cancelled)

9. (Currently Amended) The apparatus according to claim 7, wherein ~~said~~ the sub-lookup table stores the address of an entry in which the first and second color difference values are the same.